WATER PRO

Great Water, Great Life.

Commercial Reverse Osmosis

Unit	LP-2800	HP-2200
Membrane Size	4x40 low pressure	4x40 high pressure
GPD	2,800	2,200
Production GPM	2	1.52
Rejection GPM	6	3.48
Total GPM	8	5
Recovery	25%	30%
Operating PSI	115	225
Motor Horse	0.5 hp	1 hp
Volts	115/230	115/230
Amps	10.8/5.4	16.2/8.1
Connection Feed	3/4”	3/4”
Connection Product	1/2"	1/2"
Pump Model	7GBS05FS	7GBS10FS
Pre-Filter Size	2x20	2x20
Dimensions WxDxH	18x23x55	18x23x55
Approx. Unit Weight	120 lbs.	120 lbs.

Built in the USA

*NSF Certified Membrane
*Stainless Steel Membrane Housing
*Gould’s Multi Stage SS Centrifugal Pump
*TDS Monitor for Product and Feed
*Low Pressure Safety Cut Off
*Product and Drain Flow Meters
*Stainless Steel Drain Valve
*2” x 20” Sediment Pre Filter
*Inlet Solenoid Valve
*SS Operating Pressure Gauge
*Comprehensive Warranty
*Easy to Install and Maintain
*Aluminum Frame

Optional Features:

*Auto Flush
*Waste Recycle
*Pre Filter Gauge
*Control Panel
*Powder Coating
(*custom colors*)

Low Pressure Units are based on 500ppm properly pre-treated water at 115psi operating pressure and 77° water.
High Pressure Units are based on 2000ppm properly pre-treated water at 225psi operating pressure and 77° water.

Phone: 804-693-7294
info@WaterProInc.com

9977 John Clayton Memorial Hwy
Gloucester, Virginia 23061

www.WaterProInc.com