

## Whole House Reverse Osmosis

Unit	LP-2800	HP-2200
Membrane Size		
	4x40 low pressure	4x40 high pressure
GPD	2,800	2,200
Production GPM	2	1.52
Rejection GPM	6	3.48
Total GPM	8	5
Recovery	25%	30%
Operating PSI	115	225
Motor Horse	0.5 hp	1 hp
Volts	115/230	115/230
Amps	10.8/5.4	16.2/8.1
Connection Feed	3/4"	3/4"
Connection Product	1/2"	1/2"
Pump Model	7GBS05FS	7GBS10FS
Pre-Filter Size	2x20	2x20
Dimensions WxDxH	18x23x55	18x23x55
Approx. Unit Weight	120 lbs.	120 lbs.



Built in the USA

\*NSF Certified Membrane \*Stainless Steel Membrane Housing \*Gould's Multi Stage SS Centrifugal Pump \*TDS Monitor for Product and Feed \*Low Pressure Safety Cut Off \*Product and Drain Flow Meters \*Stainless Steel Drain Valve \*2" x 20" Sediment Pre Filter \*Inlet Solenoid Valve \*SS Operating Pressure Gauge \*Comprehensive Warranty \*Easy to Install and Maintain \*Aluminum Frame

## **Optional Features:**

\*Auto Flush \*Waste Recycle \*Pre Filter Gauge \*Control Panel \*Powder Coating (custom colors)

**Low Pressure Units** are based on 500ppm properly pre-treated water at 115psi operating pressure and 77° water. **High Pressure Units** are based on 2000ppm properly pre-treated water at 225psi operating pressure and 77° water.

## Phone: 804-693-7294 info@WaterProInc.com

## 9977 John Clayton Memorial Hwy Gloucester, Virginia 23061

www.WaterProInc.com